

## **FARMALL JXM**

TRACTORS 80 - 90 HP



SPECIFICATIONS	FARMALL JXM 80	FARMALL JXM 90	
ENGINE			
Model	\$8	\$8000	
Emission	Tie	Tier III	
No. of cylinders/ aspiration	4 / Turbochar	4 / Turbocharged Aftercooled	
Capacity/Bore x stroke(cm <sup>3</sup> ) / (mm)	3908 / 1	3908 / 104 x 115	
Engine rated power @ 2300 rpm (kW/hp)	59.7 / 80	67.2 / 90	
Maximum torque at 1400 rpm (Nm)	310	340	
Fuel tank capacity (L)		90	
TRANSMISSION			
Transmission Type	Synchromesh gea	Synchromesh gears + Power Shuttle	
Clutch Type	Mechanical Double clutch / Power Shut	Mechanical Double clutch / Power Shuttle main clutch & Mechanical PTO clutch	
No of Gears	12F	12F+12R	
Optional Speeds	8F+8R,12F+12R Cree	8F+8R,12F+12R Creeper, 20F+20R Creeper	
PTO Control of the co			
Standard	5	540	
Optional	540/540E	540/540E & 540/1000	
Туре	Reversible /	Reversible / Ground Speed	
HYDRAULICS			
Draft sensing	Тор	Top Link	
Rear linkage category	I	I-II	
Stabiliser & Link ends	Chain - Fixed / Te	Chain - Fixed / Telescopic - Flexible	
Mechanical lift control	Position, draft, mixe	Position, draft, mixed / Fast Raise-Lower	
Main pump flow – standard (l/min)	54, 6	54, 60 (Opt)	
Steering pump flow (I/min)	26	26/31	
Maximum number of remote valves		3	
Maximum lift capacity at ball ends with arms horizontal (kg)	25	2500	
AXLES			
Front	2/4	2 / 4 WD	
Rear	Heavy Duty	Heavy Duty straight axle	
DIMENSIONS & WEIGHT			
Wheel Base 2WD (mm)	22	2283	
Wheel Base 4WD (mm)	22	2258	
Total Weight 2WD (kg)	28	2825	
Total Weight 4WD (kg)	30	3085	

SAFETY NEVER HURTSI<sup>TM</sup> Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. This literature has been published for worldwide circulation. The standard and optional equipment and the availability of individual models may vary from one country to the next. Case IH reserves the right to undertake modifications without prior notice to the design and technical equipment at all times without this resulting in any obligation whatsoever to make such modifications to units already sold. Whilst every effort is made to ensure that the specifications, descriptions and illustrations in this brochure are correct at the time of going to press, these are also subject to change without prior notice. Illustrations may show optional equipment or may not show all standard equipment. Case IH recommends AKCELA lubricants. CNH International Asia, Middle East and Africa - Riva Paradiso, 14 - 6902 Paradiso-Lugano Switzerland - Visit our website: www.caseih.com - Case IH Farmall JXM Brochure 08/20 AMEA - 20AMEAMEAJXMO01







## Kinshasa

169, Boulevard du 30 juin Kinshasa - Gombe **084.845.51.42**  4479, Avenue Militant Kinshasa - Ndolo **089.011.31.57** 

## Lubumbashi

741, Route Likasi Commune de Lubumbashi **085.577.53.00**  www.congo-motors.com equipments@congo-motors.com info@congo-motors.com